



An ISO 9001 : 2015 Certified Company

TALON-X (SRL) Polymer Casing with GI wire/cable with inbuilt handle

Ref: SF-RFA-40FT to SF-RFA-60FT

TALON-X 40 to 60 FT' Galvanized Wire Cable SRL with High Impact Strength Polymer Housing with Built-in Handle, swivel eye at anchorage end, other end with load indicator swivel snap hook. Includes one (1) quarter turn locking Karabiner SF-1101 A(C).

DESIGN

- Quick activating breaking mechanism components.
- Robust & durable plastic casing
- Has swivel anchorage eye at anchorage end
- Steel snap hook at retractable end (Our ref. SF-1404 as per ANSI Z359.12-2009 gate strength 3600 lbs.
- Galvanized steel wire rope

LENGTH

- 40 ft to 60 ft.

CABLE

- Material: Galvanized steel wire rope Ø3/16 Inches
- Minimum Breaking strength: 3600 lbs.

WEIGHT

- SF-RFA-40FT :- 14.462 lbs ± 0.22 lbs.
- SF-RFA-50FT :- 14.991 lbs ± 0.22 lbs.
- SF-RFA-60FT :- 15.586 lbs ± 0.22 lbs.

USER CAPACITY

- ANSI User Capacity: 310 lbs. Max.

RELEVANT STANDARDS

- Meets or Exceeds ANSI Z359.14-2021 CLASS 1.



TECHNICAL DATA SHEET

FALL PROTECTION EQUIPMENTS

